




LINEA 42

LT | Prie lubų montuojami šviestuvai su LED šviesos šaltiniais, šviesos spalvos temperatūra 3000 K, pagal specialų užsakymą gali būti su 4000 K spalvine temperatūra. Spalvų atgaiva CRI 80. Šviesos sklaidytuvas iš opalinio arba iš akinimą ribojančio mikroprizmatinio sklaidytuvo su optine plėvele. Pagal užsakymą gaminami reguliuojamo šviesos srauto variantai (DALI). Šviesos srauto reguliavimo diapazonas nuo 1 iki 100%. Tarnavimo trukmė 50 000 val. (L80/B10). Šviestuvo aliuminio profilio korpusas dažomas milteliniais dažais, standartinės spalvos – balta ir juoda. Elektrosaugos klasė I, apsaugos laipsnis IP20


EN | Surface mounted luminaire made of solid aluminium body. Luminaire with LED light sources, light colour temperature 3000K. Light colour temperature of 4000K available on request. Luminaire optic with opal plastic diffuser or glare limiting microprismatic single illuminated surface lens with optical film. DALI control interface, control range from 1 to 100%, constant light flux keeping function. Lifetime 50 000 hours (L80/B10). Standard colours: powder painted white, black, other colours on request. Electrical safety class I. Protection degree IP20.




LINEA 42 60 DIR MP




LINEA 42 60 DIR OP



Vaizdas iš šviestuvo šono | Side view



 LED	Modelis Model	W	lm	Balastas Ballast	Švietimo kryptis Distribution	Skaidytuvas Diffuser	L, mm	Kodas Code
LINEA 42 60	15	1685	1381	ON/OFF	Tiesioginė direct	Opalinis Opal	574	M060S0150DOP00*L0
						Mikroprizmatinis Conical Prism		M060S0150DMP00*L0
		1685	1381	DALI		Opalinis Opal		M060S0150DOP00*L1
						Mikroprizmatinis Conical Prism		M060S0150DMP00*L1
LINEA 42 90	22	2528	2071	ON/OFF	Tiesioginė direct	Opalinis Opal	854	M090S0220DOP00*L0
						Mikroprizmatinis Conical Prism		M090S0220DMP00*L0
		2528	2071	DALI		Opalinis Opal		M090S0220DOP00*L1
						Mikroprizmatinis Conical Prism		M090S0220DMP00*L1
LINEA 42 120	29	3371	2761	ON/OFF	Tiesioginė direct	Opalinis Opal	1134	M120S0290DOP00*L0
						Mikroprizmatinis Conical Prism		M120S0290DMP00*L0
		3371	2761	DALI		Opalinis Opal		M120S0290DOP00*L1
						Mikroprizmatinis Conical Prism		M120S0290DMP00*L1
LINEA 42 140	36	4214	3452	ON/OFF	Tiesioginė direct	Opalinis Opal	1414	M140S0360DOP00*L0
						Mikroprizmatinis Conical Prism		M140S0360DMP00*L0
		4214	3452	DALI		Opalinis Opal		M140S0360DOP00*L1
						Mikroprizmatinis Conical Prism		M140S0360DMP00*L1
LINEA 42 280	72	8427	6904	ON/OFF	Tiesioginė direct	Opalinis Opal	2814	M280S0720DOP00*L0
						Mikroprizmatinis Conical Prism		M280S0720DMP00*L0
		8427	6904	DALI		Opalinis Opal		M280S0720DOP00*L1
						Mikroprizmatinis Conical Prism		M280S0720DMP00*L1

* - Spalva | Colour: W-balta | white (RAL-9016); B-juoda | black (RAL-9005)