


LINEA fiksuoto ilgio | fixed length

LT | Prie lubų montuojami šviestuvai LINEA su LED šviesos šaltiniais, šviesos spalvos temperatūra 3000 K, pagal specialų užsakymą gali būti su 4000 K spalvine temperatūra. Spalvų atgaiva CRI 80. Šviesos sklaidytuvus iš opalinio arba iš akinimą ribojančio mikroprizmatinis sklaidytuvus su optine plėvele. Pagal užsakymą gaminami reguliuojamo šviesos srauto variantai (DALI). Šviesos srauto reguliavimo diapazonas nuo 1 iki 100%. Tarnavimo trukmė 50 000 val. (L80/B10). Šviestuvo aliuminio profilio korpusas dažomas milteliniais dažais, standartinės spalvos - balta, juoda arba pilka. Elektrosaugos klasė I, apsaugos laipsnis IP20


EN | Surface mounted LINEA luminaire made of solid aluminium body. Luminaire with LED light sources, light colour temperature 3000K. Light colour temperature of 4000K available on request. Luminaires optic with opal plastic diffuser or glare limiting microprismatic single illuminated surface lens with optical film. DALI control interface, control range from 1 to 100%, constant light flux keeping function. Lifetime 50 000 hours (L80/B10). Standard colours: grey, powder painted white, black, other colours on request. Electrical safety class I. Protection degree IP20.




Vaizdas iš šviestuvo šono | Side view




LINEA 140 ME DIR OP



LINEA 140 ME DIR MP



 LED	Modelis Model	W	lm	Balastas Ballast	Švietimo kryptis Distribution	Sklandytuvus Diffuser	L, mm	Kodas Code
LINEA 120 ME	20	2342	ON/OFF	Tiesioginė direct	Opalinis Opal	1128	L120S1250DOP00*L0	
		1932			Mikroprizmatinis Conical Prism		L120S1250DCP00*L0	
		2342	DALI		Opalinis Opal		L120S1250DOP00*L1	
		1932			Mikroprizmatinis Conical Prism		L120S1250DCP00*L1	
LINEA 140 ME	25	2928	ON/OFF	Tiesioginė direct	Opalinis Opal	1408	L140S1310DOP00*L0	
		2415			Mikroprizmatinis Conical Prism		L140S1310DCP00*L0	
		2928	DALI		Opalinis Opal		L140S1310DOP00*L1	
		2415			Mikroprizmatinis Conical Prism		L140S1310DCP00*L1	
LINEA 220 ME	40	5023	ON/OFF	Tiesioginė direct	Opalinis Opal	2250	L220S2190DOP00*L0	
		3952			Mikroprizmatinis Conical Prism		L220S2190DCP00*L0	
		5023	DALI		Opalinis Opal		L220S2190DOP00*L1	
		3952			Mikroprizmatinis Conical Prism		L220S2190DCP00*L1	
LINEA 280 ME	50	5855	ON/OFF	Tiesioginė direct	Opalinis Opal	2810	L280S2230DOP00*L0	
		4830			Mikroprizmatinis Conical Prism		L280S2230DCP00*L0	
		5855	DALI		Opalinis Opal		L280S2230DOP00*L1	
		4830			Mikroprizmatinis Conical Prism		L280S2230DCP00*L1	


* - Spalva | Colour: W-balta | white (RAL 9016); B-juoda | black (RAL 9005); G-pilka | grey (RAL 9006)

 **LED**
Modelis |
Model


Modelis Model	W	lm	Balastas Ballast	Švietimo kryptis Distribution	Skaidytuvai Diffuser	L, mm	Kodas Code
LINEA 420 ME	73	8783	ON/OFF	Tiesioginė direct	Opalinis Opal	4210	L420S0730DOP00*L0
		7245			Mikroprizmatinis Conical Prism		L420S0730DCP00*L0
		8783	DALI		Opalinis Opal		L420S0730DOP00*L1
		7245			Mikroprizmatinis Conical Prism		L420S0730DCP00*L1

* - Spalva | Colour: W-balta | white (RAL 9016); B-juoda | black (RAL 9005)

LINEA 140 HO DIR OP



LINEA 140 HO DIR MP



 **LED**
Modelis |
Model

Modelis Model	W	lm	Balastas Ballast	Švietimo kryptis Distribution	Skaidytuvai Diffuser	L, mm	Kodas Code
LINEA 120 HO	29	3513	ON/OFF	Tiesioginė direct	Opalinis Opal	1128	L120S0290DOP00*L0
		2901			Mikroprizmatinis Conical Prism		L120S0290DCP00*L0
		3513	DALI		Opalinis Opal		L120S0290DOP00*L1
		2901			Mikroprizmatinis Conical Prism		L120S0290DCP00*L1
LINEA 140 HO	36	4391	ON/OFF	Tiesioginė direct	Opalinis Opal	1408	L140S0360DOP00*L0
		3626			Mikroprizmatinis Conical Prism		L140S0360DCP00*L0
		4391	DALI		Opalinis Opal		L140S0360DOP00*L1
		3626			Mikroprizmatinis Conical Prism		L140S0360DCP00*L1
LINEA 170 HO	43	5270	ON/OFF	Tiesioginė direct	Opalinis Opal	1690	L170S0430DOP00*L0
		4352			Mikroprizmatinis Conical Prism		L170S0430DCP00*L0
		5270	DALI		Opalinis Opal		L170S0430DOP00*L1
		4352			Mikroprizmatinis Conical Prism		L170S0430DCP00*L1
LINEA 280 HO	72	8783	ON/OFF	Tiesioginė direct	Opalinis Opal	2810	L280S0720DOP00*L0
		7253			Mikroprizmatinis Conical Prism		L280S0720DCP00*L0
		8783	DALI		Opalinis Opal		L280S0720DOP00*L1
		7253			Mikroprizmatinis Conical Prism		L280S0720DCP00*L1
LINEA 420 HO	108	13174	ON/OFF	Tiesioginė direct	Opalinis Opal	4210	L420S1080DOP00*L0
		10879			Mikroprizmatinis Conical Prism		L420S1080DCP00*L0
		13174	DALI		Opalinis Opal		L420S1080DOP00*L1
		10879			Mikroprizmatinis Conical Prism		L420S1080DCP00*L1

* - Spalva | Colour: W-balta | white (RAL 9016); B-juoda | black (RAL 9005)